

# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03  
Version: 4.0

Page: 1/10  
(30288739/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

### SPRAYTITE\* 178-F B-RESIN

#### Recommended use of the chemical and restriction on use

Recommended use\*: polyurethane component; industrial chemicals  
Suitable for use in industrial sector: Polymers industry; chemical industry

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

Company:  
BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

CHEMTRIC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Chemical family: Preparation based on: polyol, catalyst, stabilizing agents, flameproofing agent, propellant  
Synonyms: Urethane System Resin Component

### 2. Hazards Identification

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Repr.	2 (unborn child)	Reproductive toxicity
STOT RE	2 (oral)	Specific target organ toxicity — repeated exposure

# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03

Version: 4.0

Page: 2/10  
(30288739/SDS\_GEN\_US/EN)

### Label elements

Pictogram:



Signal Word:  
Warning

Hazard Statement:

H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H361 Suspected of damaging the unborn child.  
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure (oral).

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P260 Do not breathe dust/gas/mist/vapours.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical advice/attention if you feel unwell.  
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

### Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

### 3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
78-40-0	>= 10.0 - < 15.0%	Triethyl phosphate
460-73-1	>= 7.0 - < 10.0%	Propane, 1,1,1,3,3-pentafluoro-
111-46-6	>= 1.0 - < 5.0%	diethylene glycol
108-01-0	>= 1.0 - < 3.0%	2-dimethylaminoethanol

# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03

Version: 4.0

Page: 3/10

(30288739/SDS\_GEN\_US/EN)

2212-32-0	>= 0.2 - < 0.3%	2-((2-(dimethylamino)ethyl)methylamino)ethanol
8052-41-3	>= 0.1 - < 0.2%	Stoddard solvent
149-57-5	>= 0.0 - < 0.2%	2-ethylhexanoic acid

The product contains:

<b>CAS Number</b>	<b>Weight %</b>	<b>Chemical name</b>
25265-71-8	< 2.0%	dipropylene glycol

---

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

Remove contaminated clothing.

#### If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

#### If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

#### If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

#### If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

#### Information on: diethylene glycol

*Symptoms: Overexposure may cause: vomiting, coma, abdominal cramps, lethargy, nausea, diarrhea, headache*

#### Information on: 2-dimethylaminoethanol

*Symptoms: Overexposure may cause: shortness of breath, restlessness, coughing, headache*

---

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03  
Version: 4.0

Page: 4/10  
(30288739/SDS\_GEN\_US/EN)

Suitable extinguishing media:  
water spray, dry powder, carbon dioxide, foam

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
No particular hazards known.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## 6. Accidental release measures

Further accidental release measures:  
High risk of slipping due to leakage/spillage of product.

### Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

### Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

### Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

---

## 7. Handling and Storage

### Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Protect against moisture.

Protection against fire and explosion:  
No explosion proofing necessary.

### Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids. Segregate from oxidants.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2)

Further information on storage conditions: Product that is frozen and/or tending to sedimentation can be liquified or homogenized by careful application of indirect heat (do not use flames or direct contact with a heat source). Protect from direct sunlight. Keep in a cool, well-ventilated place. Avoid extreme heat. Store protected against freezing. Stored and transported in a cylinder under pressure. Must not be repacked by the customer.

Storage stability:  
Storage temperature: 70 - 80 °F  
Protect against moisture.  
Store in unopened original containers in a cool and dry place.

# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03  
Version: 4.0

Page: 5/10  
(30288739/SDS\_GEN\_US/EN)

The stated storage temperature is noted for health and safety in the workplace. With regard to Quality, please refer to the product specific Technical Bulletin.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

2-ethylhexanoic acid

ACGIH TLV      TWA value 5 mg/m<sup>3</sup> Inhalable fraction and vapor ;

Stoddard solvent

OSHA PEL      PEL 500 ppm 2,900 mg/m<sup>3</sup> ;  
ACGIH TLV      TWA value 100 ppm ;

#### **Advice on system design:**

Provide local exhaust ventilation to control vapours/mists.

#### Personal protective equipment

##### **Respiratory protection:**

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

##### **Hand protection:**

Chemical resistant protective gloves

##### **Eye protection:**

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

##### **Body protection:**

Standard work clothes and shoes.

#### **General safety and hygiene measures:**

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

### 9. Physical and Chemical Properties

Form:	liquid
Odour:	mild, amine-like
Odour threshold:	not applicable
Colour:	various, depending on the colourant
pH value:	>= 7
Freezing point:	Unspecified
Boiling point:	Unspecified
Sublimation point:	No applicable information available.
Flash point:	> 200 °F > 93.3 °C
Flammability:	not flammable
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.
Upper explosion limit:	For liquids not relevant for classification and labelling.
Autoignition:	Unspecified

# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03

Version: 4.0

Page: 6/10

(30288739/SDS\_GEN\_US/EN)

---

Vapour pressure:	Unspecified
Density:	9.60 - 9.83 lb/USg ( 25 °C)
Relative density:	No applicable information available.
Vapour density:	not applicable
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Self-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	350 - 650 mPa.s ( 21 °C)
Viscosity, kinematic:	No applicable information available.
Solubility in water:	slightly soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

---

## 10. Stability and Reactivity

### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### Corrosion to metals:

No corrosive effect on metal.

### Oxidizing properties:

not fire-propagating

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

The product is chemically stable.

### Conditions to avoid

> 80 degrees Fahrenheit

Avoid moisture. Avoid direct sunlight. Avoid excessive temperatures.

### Incompatible materials

acids, oxidizing agents, isocyanates

### Hazardous decomposition products

#### Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide

#### Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03  
Version: 4.0

Page: 7/10  
(30288739/SDS\_GEN\_US/EN)

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: No known acute effects.

##### Oral

No applicable information available.

##### Inhalation

No applicable information available.

##### Dermal

No applicable information available.

##### Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Origin of data: expert judgement

##### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

##### *Information on: 2-dimethylaminoethanol*

Assessment of irritating effects: *Corrosive! Damages skin and eyes.*

##### *Information on: 2-((2-(dimethylamino)ethyl)methylamino)ethanol*

Assessment of irritating effects: *Skin contact causes irritation. May cause severe damage to the eyes.*

---

##### Sensitization

Assessment of sensitization: The chemical structure does not suggest a sensitizing effect. No applicable information available.

##### Aspiration Hazard

No aspiration hazard expected.

#### Chronic Toxicity/Effects

##### Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

##### *Information on: diethylene glycol*

Assessment of repeated dose toxicity: *The substance may cause damage to the kidney after repeated ingestion.*

*The substance may cause damage to the liver after repeated ingestion.*

---

# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03  
Version: 4.0

Page: 8/10  
(30288739/SDS\_GEN\_US/EN)

### Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

### Teratogenicity

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

### *Information on: 2-ethylhexanoic acid*

*Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.*

---

### Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

## Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

## 12. Ecological Information

### Toxicity

#### Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

### Persistence and degradability

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

Poorly biodegradable.

#### Elimination information

Poorly biodegradable.

### Bioaccumulative potential

#### Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

### Mobility in soil

#### Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.



# Safety Data Sheet

## SPRAYTITE® 178-F B-RESIN

Revision date : 2016/06/03

Version: 4.0

Page: 10/10  
(30288739/SDS\_GEN\_US/EN)

Health : 2      Fire: 1      Reactivity: 1      Special:

### HMIS III rating

Health: 2       Flammability: 1      Physical hazard: 1

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2016/06/03

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

SPRAYTITE is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET