

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date : 2025/03/11

Version: 6.0

Page: 1/12

(30837660/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

WALLTITE® MAX R RESIN

Recommended use of the chemical and restriction on use

Recommended use*: polyurethane component; industrial chemicals

Suitable for use in industrial sector: Polymers industry; chemical industry

Unsuitable for use: Uses other than recommended

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION

100 Park Avenue

Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information

CHEMREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: resin

Synonyms: Urethane System Resin Component

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Eye Dam.	1	Serious eye damage
Skin Irrit.	2	Skin irritation
Skin Sens.	1	Skin sensitization
Repr.	2 (fertility)	Reproductive toxicity

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11

Version: 6.0

Page: 2/12

(30837660/SDS_GEN_US/EN)

Repr.	2 (unborn child)	Reproductive toxicity
Carc.	2	Carcinogenicity

Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility. Suspected of damaging the unborn child.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P201	Obtain special instructions before use.
P261	Avoid breathing mist or vapour or spray.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.
P308 + P313	IF exposed or concerned: Get medical attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11

Version: 6.0

Page: 3/12

(30837660/SDS_GEN_US/EN)

Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol

CAS Number: 940912-28-7

Content (W/W): >= 15.0 - < 25.0%

Synonym: (POLYMER) Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol

Halogenated hydrocarbon

CAS Number: Trade Secret

Content (W/W): >= 10.0 - < 15.0%

Synonym: No data available.

Alkyl halide Phosphate

CAS Number: Trade Secret

Content (W/W): >= 3.0 - < 7.0%

Synonym: No data available.

Alkylenediamine polymer with alkoxides

CAS Number: Trade Secret

Content (W/W): >= 1.0 - < 5.0%

Synonym: No data available.

Hydroxyalkyl ether

CAS Number: Trade Secret

Content (W/W): >= 0.3 - < 3.0%

Synonym: No data available.

Morpholine derivative

CAS Number: Trade Secret

Content (W/W): >= 1.0 - < 5.0%

Synonym: No data available.

Hexanoic acid, 2-ethyl-, bismuth(3+) salt

CAS Number: 67874-71-9

Content (W/W): >= 1.0 - < 3.0%

Synonym: No data available.

Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide

CAS Number: 34354-45-5

Content (W/W): > 0.0 - < 3.0%

Synonym: (POLYMER) Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11

Version: 6.0

Page: 4/12

(30837660/SDS_GEN_US/EN)

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Remove contact lenses, if present. Immediate medical attention required.

If swallowed:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., corneal injury, skin irritation, Skin contact may provoke the following symptoms:, allergic symptoms

Information on: Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol

Symptoms: Ingestion may cause gastrointestinal irritation with nausea, vomiting and diarrhea., skin irritation, corneal injury

Information on: Alkylenediamine polymer with alkoxides

Symptoms: No data available.

Information on: Morpholine derivative

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: Hexanoic acid, 2-ethyl-, bismuth(3+) salt

Symptoms: Overexposure may cause:, corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide

Symptoms: skin irritation, corneal injury, Ingestion may cause gastrointestinal irritation with nausea, vomiting and diarrhea.

Information on: Hydroxyalkyl ether

Symptoms: Overexposure may cause:, vomiting, coma, abdominal cramps, lethargy, nausea, diarrhea, headache

Information on: Alkyl halide Phosphate

Symptoms: Overexposure may cause:, convulsions, depression, hypoxemia, tremors

Hazards: Symptoms can appear later.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11
Version: 6.0

Page: 5/12
(30837660/SDS_GEN_US/EN)

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Avoid inhalation of mists/vapours. When using do not eat, drink or smoke. Wear suitable gloves and eye/face protection. Protect against moisture.

Protection against fire and explosion:
No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2)

Further information on storage conditions: From this information no suitability of the materials mentioned above for the design of installations, including containers for permanent storage, can be

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11

Version: 6.0

Page: 6/12

(30837660/SDS_GEN_US/EN)

inferred. Special conditions apply to the selection of materials in this regard, which we can communicate on request.

Containers should be stored tightly sealed in a dry place.

Storage stability:

Storage temperature: 16 - 27 °C

Protect against moisture.

The stated storage temperature is noted for health and safety in the workplace. With regard to Quality, please refer to the product specific Technical Bulletin.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Chemical resistant protective gloves, Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:

Standard work clothes and shoes., Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately. Do not eat, drink or use tobacco while working. Wash thoroughly after handling.

9. Physical and Chemical Properties

Form:	liquid
Odour:	amine-like
Odour threshold:	No applicable information available.
Colour:	amber
pH value:	>= 7
Freezing point:	0.00 °C
Melting point:	No data available.
Boiling point:	100.00 °C
Sublimation point:	No applicable information available.
Flash point:	> 94.00 °C
Flammability:	not flammable
	(closed cup) (derived from flash point)

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11

Version: 6.0

Page: 7/12

(30837660/SDS_GEN_US/EN)

Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.
Upper explosion limit:	For liquids not relevant for classification and labelling.
Autoignition:	Unspecified
Vapour pressure:	< 0.1 hPa (25 °C)
Density:	1.1000 g/cm ³ (25.00 °C)
Relative density:	No applicable information available.
Vapour density:	No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Self-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	600 - 800 mPa.s (23.00 °C)
Viscosity, kinematic:	not determined
Solubility in water:	partly soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	No data available.
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Temperature: < 0 degrees Celsius

Incompatible materials

acids, oxidizing agents, isocyanates

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11
Version: 6.0

Page: 8/12
(30837660/SDS_GEN_US/EN)

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Oral

Type of value: ATE

Value: 3,787 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

No applicable information available.

Dermal

Type of value: ATE

Value: > 5,000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Origin of data: expert judgement

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: Alkylenediamine polymer with alkoxides

Assessment of irritating effects: May cause slight irritation to the skin. Eye contact causes irritation.

Information on: Morpholine derivative

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes slight irritation.

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11

Version: 6.0

Page: 9/12

(30837660/SDS_GEN_US/EN)

Information on: Hexanoic acid, 2-ethyl-, bismuth(3+) salt

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Information on: Alkylenediamine polymer with alkoxides

*Assessment of sensitization:
sensitizing effect in animal tests*

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Information on: Hydroxyalkyl ether

Assessment of repeated dose toxicity: The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies. The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The effects were only observed at doses/concentrations not relevant for classification and/or practical use conditions. These effects are not relevant to humans at occupational levels of exposure.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Information on: Alkyl halide Phosphate

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.

Information on: Hexanoic acid, 2-ethyl-, bismuth(3+) salt

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11

Version: 6.0

Page: 10/12
(30837660/SDS_GEN_US/EN)

Teratogenicity

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Information on: Hexanoic acid, 2-ethyl-, bismuth(3+) salt

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Medical conditions aggravated by overexposure

Individuals with allergic history or pre-existing dermatitis should use extra precautions when handling this product. The substance may cause sensitization of the skin in particularly sensitive individuals.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11
Version: 6.0

Page: 11/12
(30837660/SDS_GEN_US/EN)

Do not allow to enter soil, waterways or waste water channels. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

13. Disposal considerations

Waste disposal of substance:

Incinerate or dispose of in a licensed facility. Do not discharge substance/product into sewer system.

Container disposal:

Do not reuse empty containers. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US

All substances are TSCA listed and active.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

State RTK

PA

CAS Number

Trade Secret

123-91-1

Chemical name

Hydroxalkyl ether

1,4-dioxane

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including 1,4-DIOXANE, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

Safety Data Sheet

WALLTITE® MAX R RESIN

Revision date: 2025/03/11

Version: 6.0

Page: 12/12

(30837660/SDS_GEN_US/EN)

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 1 Special:

HMIS III rating

Health: 3¤ Flammability: 1 Physical hazard: 1

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2025/03/11

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

WALLTITE® MAX R RESIN is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED
HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS
PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT
PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO
DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR
TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING
WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE
MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET
FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED
WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE
SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED
A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY
UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION
FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO
OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION
GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
BASF CORPORATION WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR
USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR
PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH
INTERNAL BODILY TISSUES OR FLUIDS.

END OF DATA SHEET