



# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)  
Issue date: 2025-09-08 Version: 1.0

## SECTION 1: Identification

### 1.1. Product identifier

Trade name : CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g  
Product code : 1006202  
Part number : 73330

### 1.2. Recommended use and restrictions on use

Recommended use : Lubricating grease  
Restrictions on use : None known

### 1.3. Supplier

#### Manufactured or sold by:

CRC Canada Co.  
83 Galaxy Blvd.  
Unit 35 - 37  
Toronto, ON M9W 5X6  
Canada  
T 416-847-7750  
[crcindustries.ca](http://crcindustries.ca)

### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)  
24-Hour Emergency

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

#### Classification (GHS CA)

Acute toxicity (inhalation), Category 4	Harmful if inhaled.
Skin corrosion/irritation, Category 2	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	Causes serious eye irritation.

### 2.2. GHS Label elements, including precautionary statements

#### GHS CA labeling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Warning

Hazard statements (GHS CA)

: Causes skin irritation  
Causes serious eye irritation  
Harmful if inhaled  
: Avoid breathing vapors.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves, eye and face protection.  
Wash hands thoroughly after handling.

Precautionary statements (GHS CA)

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice or attention.  
IF ON SKIN: Wash with plenty of water.  
If skin irritation occurs: Get medical advice or attention.  
Take off contaminated clothing and wash it before reuse.  
Dispose of contents/container in accordance with local/regional/national regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Distillates (petroleum), hydrotreated heavy naphthenic	Distillates (petroleum), hydrotreated heavy naphthenic	CAS-No.: 64742-52-5	45 – 70
Molybdenum sulfide (MoS <sub>2</sub> )	Molybdenum sulfide	CAS-No.: 1317-33-5	1 – 5
Lithium hydroxide monohydrate	Lithium hydroxide	CAS-No.: 1310-66-3	1 – 5
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts	CAS-No.: 68649-42-3	1 – 5
Quartz (SiO <sub>2</sub> )	Quartz (SiO <sub>2</sub> )	CAS-No.: 14808-60-7	0.1 – 1
Distillates (petroleum), solvent-refined heavy paraffinic	Distillates (petroleum), solvent-refined heavy paraffinic	CAS-No.: 64741-88-4	0.1 – 1

Comments

: The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact : Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

First-aid measures after ingestion	: Rinse mouth. Never give anything by mouth to an unconscious person. Do not induce vomiting without advice from poison control center. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Harmful if inhaled.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract.

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	: Do not use a heavy water stream.
--------------------------------	------------------------------------

### 5.3. Specific hazards arising from the hazardous product

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
------------------	---

### 6.2. Methods and materials for containment and cleaning up

For containment	: Stop leak, if possible without risk. Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
Additional Regulatory Information	: Dispose of materials or solid residues at an authorized site.

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling

- : Avoid contact with skin and eyes. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
- : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

- : Keep in a cool, well-ventilated place away from heat.

Storage conditions

- : Store in a cool, dry place out of direct sunlight.

Packaging materials

- : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Quartz (SiO<sub>2</sub>) (14808-60-7)

##### Canada (Alberta) - Occupational Exposure Limits

Local name	Silica-Crystalline: Quartz
OEL TWA	0.025 mg/m <sup>3</sup> Respirable particulate
Notations and remarks	Carcinogenicity A2
Regulatory reference	Alberta Regulation 191/2021

##### Canada (Quebec) - Occupational Exposure Limits

Local name	Silica - Crystalline, Quartz
VEMP (OEL TWAEV)	0.1 mg/m <sup>3</sup> Rd
Notations and remarks	C2, EM
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety

##### Canada (British Columbia) - Occupational Exposure Limits

Local name	Silica, Crystalline - alpha quartz
OEL TWA	0.025 mg/m <sup>3</sup> Respirable
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Quartz (SiO<sub>2</sub>) (14808-60-7)</b>	
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m <sup>3</sup> (respirable fraction)
Notations and remarks	Designated substance
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m <sup>3</sup> (respirable fraction)
Notations and remarks	Designated substance
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Silica, Crystalline - Quartz
OEL TWAEV	0.1 mg/m <sup>3</sup> (R - Respirable fraction)
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - O. Reg. 490/09: Designated substances
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m <sup>3</sup> (respirable fraction)
Notations and remarks	Designated Chemical Substance
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Lithium hydroxide monohydrate (1310-66-3)</b>	
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Lithium hydroxide - Monohydrate
OEL TWAEV	1 mg/m <sup>3</sup>
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Ontario table of occupational exposure limits
<b>Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup> mist
OEL STEL	10 mg/m <sup>3</sup> mist

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

#### Canada (Quebec) - Occupational Exposure Limits

VECD (OEL STEV)	10 mg/m <sup>3</sup> mist
VEMP (OEL TWAEV)	5 mg/m <sup>3</sup> mist

#### Canada (Manitoba) - Occupational Exposure Limits

OEL TWA	5 mg/m <sup>3</sup> Inhalable fraction
---------	--

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear protective gloves such as: Neoprene. Nitrile

#### Eye protection:

Wear safety glasses with side shields (or goggles).

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Dark gray
Odor	: Mild petroleum.
Melting point	: 240 °C (464 °F) estimated
Freezing point	: No data available
Boiling point	: 360 °C (680 °F) estimated
Flammability (solid, gas)	: Not applicable
Explosion limits	: No data available
Flash point	: 150 °C (302 °F) Open Cup
Auto-ignition temperature	: 260 °C (500 °F) estimated
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: No data available
Solubility	: Water: Insoluble

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: < 0.001 kPa (<0.01 mm Hg) (at 20°C)
Evaporation rate	: No data available
Density	: No data available
Relative density	: 0.91
Relative vapor density at 20°C	: > 1 (air=1)
Particle characteristics	: No data available

### 9.2. Additional Regulatory Information

Additional information	: Form : Semi-Solid
------------------------	---------------------

## SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur, phosphorus, zinc and/ or nitrogen.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

#### Quartz (SiO<sub>2</sub>) (14808-60-7)

LD50 oral	500 mg/kg body weight
-----------	-----------------------

#### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	2.18 mg/l Source: IUCLID

#### Molybdenum sulfide (MoS<sub>2</sub>) (1317-33-5)

LD50 dermal rabbit	> 2000 mg/kg Source: ChemIDplus
LC50 Inhalation - Rat	> 2820 mg/m <sup>3</sup>

#### Lithium hydroxide monohydrate (1310-66-3)

LD50 oral rat	210 mg/kg Source: RTECS
---------------	-------------------------

#### Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

LD50 oral rat	3195 mg/kg Source: ECHA
LD50 dermal rabbit	> 3160 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 5000 mg/m <sup>3</sup> Source: ECHA

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	5.53 mg/l Source: ECHA
Skin corrosion/irritation	: Causes skin irritation.

### Lithium hydroxide monohydrate (1310-66-3)

pH	14
----	----

### Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

pH	5.5 – 7.5 Source: ECHA
Serious eye damage/irritation	: Causes serious eye irritation.

### Lithium hydroxide monohydrate (1310-66-3)

pH	14
----	----

### Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

pH	5.5 – 7.5 Source: ECHA
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.

### Quartz (SiO<sub>2</sub>) (14808-60-7)

IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens
Reproductive toxicity	: Not classified

### Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts

NOAEL (animal/female, F0/P)	300 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:
NOAEL (animal/female, F1)	1000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Aspiration hazard	: Not classified

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Viscosity, kinematic	9 – 15 mm <sup>2</sup> /s Temp.: 'other.' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
Symptoms/effects after inhalation	: Harmful if inhaled.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

### Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

LC50 - Fish [1]	1 – 5 mg/l Source: ECHA
EC50 - Crustacea [1]	1 – 1.5 mg/l Source: IUCLID
EC50 96h - Algae [1]	1 – 5 mg/l Source: IUCLID

### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

### 12.2. Persistence and degradability

#### CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

Persistence and degradability	No data is available on the degradability of this product.
-------------------------------	--

### 12.3. Bioaccumulative potential

#### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: ICSC
---	----------------------

#### Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Partition coefficient n-octanol/water (Log Pow)	14.876 Source: ECHA
---	---------------------

#### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
<b>14.1. UN number</b>		
Not regulated.	Not regulated.	Not regulated.
<b>14.2. Proper Shipping Name</b>		
Not regulated.	Not regulated.	Not regulated.
<b>14.3. Transport hazard class(es)</b>		
Not regulated.	Not regulated.	Not regulated.
<b>14.4. Packing group</b>		
Not regulated.	Not regulated.	Not regulated.
<b>14.5. Environmental hazards</b>		
No supplementary information available		

### 14.6. Special precautions for user

#### TDG

Not regulated.

#### IMDG

Not regulated.

#### IATA

Not regulated.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 15: Regulatory information

#### 15.1. National regulations

##### CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Quartz (SiO <sub>2</sub> )	14808-60-7	Listed on the Canadian DSL (Domestic Substances List)
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Listed on the Canadian DSL (Domestic Substances List)
Molybdenum sulfide (MoS <sub>2</sub> )	1317-33-5	Listed on the Canadian DSL (Domestic Substances List)
Lithium hydroxide monohydrate	1310-66-3	Not listed on the Canadian DSL (Domestic Substances List)
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	Listed on the Canadian DSL (Domestic Substances List)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Listed on the Canadian DSL (Domestic Substances List)

#### 15.2. International regulations

##### Quartz (SiO<sub>2</sub>) (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### Molybdenum sulfide (MoS<sub>2</sub>) (1317-33-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

# CRC® Moly-Graph™ Extreme Pressure Multi-Purpose Lithium Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

## 15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	0 %
Product Category	Not regulated.

## SECTION 16: Other information

Issue date : 09-08-2025

Author Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.