

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version
1.1

Revision Date:
12/04/2025

Date of last issue: 02/14/2023
Date of first issue: 02/14/2023

Print Date:
12/05/2025

SECTION 1. IDENTIFICATION

Product name : Chem-Trend SprayFoam Silicone

Manufacturer or supplier's details

Company name of supplier : Chem-Trend LP
1445 W McPherson Park Dr
PO Box 860, Howell MI 48844-0860
United States
+1 517 546 4520

E-mail address of person responsible for the SDS : SDS-NA@chemtrend.com

Emergency telephone number : +1 517 545 7070

Recommended use of the chemical and restrictions on use

Recommended use : Release agent

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aerosols : Category 1

Skin irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version
1.1

Revision Date:
12/04/2025

Date of last issue: 02/14/2023
Date of first issue: 02/14/2023

Print Date:
12/05/2025

Hazard pictograms



Signal word

: Danger

Hazard statements

: Extremely flammable aerosol.
Pressurised container: May burst if heated.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.

Precautionary statements

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
Do NOT induce vomiting.

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Naphtha (petroleum), hydrotreated light	64742-49-0*	>= 30 - < 60	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version	Revision Date:	Date of last issue: 02/14/2023	Print Date:
1.1	12/04/2025	Date of first issue: 02/14/2023	12/05/2025

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and delayed : Aspiration may cause pulmonary oedema and pneumonitis.
Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.
Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version	Revision Date:	Date of last issue: 02/14/2023	Print Date:
1.1	12/04/2025	Date of first issue: 02/14/2023	12/05/2025

Health injuries may be delayed.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Metal oxides

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

Environmental precautions : Do not allow contact with soil, surface or ground water.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version	Revision Date:	Date of last issue: 02/14/2023	Print Date:
1.1	12/04/2025	Date of first issue: 02/14/2023	12/05/2025

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Store in accordance with the particular national regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
------------	---------	------------	---------	-------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version 1.1 Revision Date: 12/04/2025 Date of last issue: 02/14/2023
Date of first issue: 02/14/2023

Print Date:
12/05/2025

		(Form of exposure)	parameters / Permissible concentration	
Naphtha (petroleum), hydrotreated light	64742-49-0	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
		TWA (Mist)	5 mg/m3	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m3	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m3	NIOSH REL (2019-10-04)
Propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL (2013-10-08)
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1 (1997-08-04)
Butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL (2013-10-08)
		STEL	1,000 ppm	ACGIH (2018-03-20)
Isobutane	75-28-5	TWA	800 ppm 1,900 mg/m3	NIOSH REL (2013-10-08)
		STEL	1,000 ppm	ACGIH (2018-03-20)

Engineering measures : Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Short term only
Combination filter:

Filter type : Filter type A-P

Hand protection

Remarks : Protective gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version 1.1	Revision Date: 12/04/2025	Date of last issue: 02/14/2023 Date of first issue: 02/14/2023	Print Date: 12/05/2025
----------------	------------------------------	---	---------------------------

concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: aerosol
Form	: Aerosol containing a compressed gas
Colour	: colourless
Odour	: hydrocarbon-like
Odour Threshold	: No data available
Melting point/ range	: No data available
Boiling point/boiling range	: > 199 °F / > 93 °C
Flammability	: Flammability (solid, gas): Not applicable
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Flash point	: 16 °F / -9 °C Method: closed cup
Auto-ignition temperature	: No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version 1.1	Revision Date: 12/04/2025	Date of last issue: 02/14/2023 Date of first issue: 02/14/2023	Print Date: 12/05/2025
----------------	------------------------------	---	---------------------------

Self-ignition	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20.5 mm ² /s (104 °F / 40 °C)
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	4,825.87 hPa (68 °F / 20 °C)
Density	:	0.64 g/cm ³ (68 °F / 20 °C)
Relative density	:	0.64 (68 °F / 20 °C)
Relative vapour density	:	No data available
Bulk density	:	No data available
Particle characteristics	:	
Other information	:	
Evaporation rate	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available
Sublimation point	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazards to be specially mentioned.
Chemical stability	:	Stable under normal conditions.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version 1.1	Revision Date: 12/04/2025	Date of last issue: 02/14/2023 Date of first issue: 02/14/2023	Print Date: 12/05/2025
----------------	------------------------------	---	---------------------------

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:
Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.
Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder, Dizziness, Drowsiness, Vomiting,
Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : This information is not available.

Components:

Naphtha (petroleum), hydrotreated light:

Species : Rabbit

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version 1.1	Revision Date: 12/04/2025	Date of last issue: 02/14/2023 Date of first issue: 02/14/2023	Print Date: 12/05/2025
----------------	------------------------------	---	---------------------------

Result : Skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Remarks : Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**IARC
OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version 1.1	Revision Date: 12/04/2025	Date of last issue: 02/14/2023 Date of first issue: 02/14/2023	Print Date: 12/05/2025
----------------	------------------------------	---	---------------------------

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

Components:

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version
1.1

Revision Date:
12/04/2025

Date of last issue: 02/14/2023
Date of first issue: 02/14/2023

Print Date:
12/05/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated light:

Biodegradability : Remarks: No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version
1.1

Revision Date:
12/04/2025

Date of last issue: 02/14/2023
Date of first issue: 02/14/2023

Print Date:
12/05/2025

Components:

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Bioconcentration factor (BCF): 10 - 2,500

Partition coefficient: n-octanol/water : log Pow: 2.2 - 5.2

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and
national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as
the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version
1.1

Revision Date:
12/04/2025

Date of last issue: 02/14/2023
Date of first issue: 02/14/2023

Print Date:
12/05/2025

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1950
Proper shipping name : Aerosols
Class : 2.1
Packing group : Not assigned by regulation
Labels : FLAMMABLE GAS
ERG Code : 126
Marine pollutant : no

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version
1.1

Revision Date:
12/04/2025

Date of last issue: 02/14/2023
Date of first issue: 02/14/2023

Print Date:
12/05/2025

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Aspiration hazard
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

WARNING: This product can expose you to chemicals including n-hexane, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version	Revision Date:	Date of last issue: 02/14/2023	Print Date:
1.1	12/04/2025	Date of first issue: 02/14/2023	12/05/2025

NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 12/04/2025

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard
- US



Chem-Trend SprayFoam Silicone

Version
1.1

Revision Date:
12/04/2025

Date of last issue: 02/14/2023
Date of first issue: 02/14/2023

Print Date:
12/05/2025

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.